

1:1 Input Range

A1SA Series

1Watt SIP4 Package Single Output, 1kVDC Isolation, Operating Temp.-40to+85°C


型名	入力電圧(V)	出力電圧(V)	出力電流(mA)	効率(%)	負荷変動率	リップルノイズ
A1SA-3.33.3	3.3	3.3	303	75-82	15% max	100mVp-p max
A1SA-3.305		5	200		15% max	
A1SA-3.312		12	84		10% max	
A1SA-3.315		15	67		10% max	
A1SA-053.3	5	3.3	303		15% max	
A1SA-0505		5	200		15% max	
A1SA-0512		12	84		10% max	
A1SA-0515		15	67		10% max	
A1SA-123.3	12	3.3	303		15% max	
A1SA-1205		5	200		15% max	
A1SA-1212		12	84		10% max	
A1SA-1215		15	67		10% max	
A1SA-243.3	24	3.3	303		15% max	
A1SA-2405		5	200		15% max	
A1SA-2412		12	84		10% max	
A1SA-2415		15	67		10% max	

1:1 Input Range

A1SA Series

1Watt SIP4 Package Single Output, 2kVDC Isolation, Operating Temp.-40to+85°C

型名	入力電圧(V)	出力電圧(V)	出力電流(mA)	効率(%)	負荷変動率	リップルノイズ
A1SA-3.33.3K2	3.3	3.3	303	75-82	15% max	100mVp-p max
A1SA-3.305K2		5	200		15% max	
A1SA-3.312K2		12	84		10% max	
A1SA-3.315K2		15	67		10% max	
A1SA-053.3K2	5	3.3	303		15% max	
A1SA-0505K2		5	200		15% max	
A1SA-0512K2		12	84		10% max	
A1SA-0515K2		15	67		10% max	
A1SA-123.3K2	12	3.3	303		15% max	
A1SA-1205K2		5	200		15% max	
A1SA-1212K2		12	84		10% max	
A1SA-1215K2		15	67		10% max	
A1SA-243.3K2	24	3.3	303		15% max	
A1SA-2405K2		5	200		15% max	
A1SA-2412K2		12	84		10% max	
A1SA-2415K2		15	67		10% max	



ピン配置

Pin	1	2	3	4
Single	-Vin	+Vin	-Vout	+Vout